

Sliding motor:

IID-SLM800–IID-SLM1000–IID-SLM1500 – IID-SLM2000



This sliding gate motor has the very stylish appearance and stronger cast aluminum base; The motor's magnetic reed switch was replaced by one small HALL limit switch plug in the control panel, and which can work more than 10 years' lifetime; The communication interface between two gate openers synchronize the double gates; Also, it has a variety of interface options for such as Bluetooth, WIFI and flashing lights.

IID-SLM800 – IID-SLM1000 – IID-SLM1500 – IID-SLM2000

Features:

- Thermal protection sensor protects the motor overheat after intensive use
- Gear motor non reversing, no need to install electric lock
- Manual open by release key on power failure
- Anti-crushing protection ensured by electronic device
- Soft start and soft stop, quiet and smooth performance

Technical data:

Model	IID-SLM800	IID-SLM1000	IID-SLM1500	IID-SLM 2000
Output torque (N.m)	22	27	35	55
Rated power (W)	370	550	750	1500
Max weight (KG)	800	1000	1500	2000
Power supply	AC220V 50Hz (AC110V 60Hz)			
Limit switch	Spring/Magnetic (NC/NO)			
Motor speed(r/min)	1400			
Gate speed(m/min)	12			
Noise(dB)	≤56			
Temperature(°C)	-40~+60			
Protection class	IP44			



www.iid2secure.nl
 Extra Benefits, Less Price
 Finestrat,19, 03530 La Nucia, Alicante, Spain
 © IID Secure Tech S.L.U. 2019

Heemdtedestraat 16 Amsterdam, Netherlands
Support@iid2secure.nl
 +31614762425
 Data Subject to change without notice