




IID-XVR04AN MODIFIED



Key Feature :

- Support H.265+ encoding (except 4K), ultra-low bitrates, compatible with H.264 surroundings
- Support VGA, HDMI full HD output simultaneously
- Support ONVIF; access third party
- Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions
- Support web, CMS, center platform management software MYEYE, provide SDK development
- Support various mobile monitoring (iPhone, Android)
- Remote Access, With DNS (ARSP), easy to monitor remotely
- Support UTC, control signal& video stream transmits through one single coaxial
- Support XVI/AHD/TVI/CVI/CVBS/IP six signals
- Support intelligent analysis: functions like Perimeter alert、item retention、Video diagnosis、intelligent fast play and intelligent

	Model	IID-XVR04AN
System	Main processor	Hi3521D
Interface	Preview	1/4/8/9
Video	Codec	H.265+
	Monitor quality	VGA(1080P at most);HDMI(4K at most)
	Preview ability	4*8M@15fps(AHD)/4*5M@20fps (6 in 1) /4*4M (6 in 1)
	Encode ability	4*8M@8fps(AHD)/4*5M@14fps (6 in 1) / 4*4M@18fps (6 in 1) /4*3M@21fps (6 in 1) /4*1080P(6 in 1)
	Decode ability	4*8M@8fps(AHD)/4*5M@14fps (6 in 1) / 4*4M@18fps (6 in 1) /4*3M@21fps (6 in 1) /4*1080P(6 in 1)
	Multi-mode input	analog : 4*8M ; 4*5M ; Digital to analog conversion : support (except 4+4 hybrid mode) Hybrid : 4*5M (analog) + 4*5M (network) 2*4K (analog) +2*4K (network) : network : 8*1080P+8*960P ; 4*5M ; 4*3M ; 4*4K
	Motion Detection	Each screen can be set to 192 (16 * 12) detection areas; multi-level sensitivity can be set (Limited local channel)
Audio	Audio compression	G.711A
	Intercom	support
Record & playback	Record mode	manual>alarm>motion detection>timing
	Local Playback	4ch(analog input mode)
	Search mode	Search by time, calendar, event, channel
Storage & backup	Video storage	HDD, network
	Backup mode	Network, USB hard disk, USB burner, SATA burner



www.iid2secure.nl

Extra Benefits, Less Price

Finestrat, 19, 03530 La Nucia, Alicante, Spain

© IID Secure Tech S.L.U. 2019

Heemtedestraat 16 Amsterdam, Netherlands

Support@iid2secure.nl

+31614762425

Data Subject to change without notice



External Interface	Video input	4ch BNC
	Video output	1ch VGA, 1ch HDMI
	Loop Vout	N/A
	Audio I/O	4/1
	Alarm I/O	0/0
	Network interface	RJ45 10M/100M self-adaption
	PTZ control	1*RS485, Support kinds of PTZ protocols
	USB	2* USB 2.0 ports
	HDD	1*SATA ports (Max 8TB/per)
	Wireless	3G, WIFI (extend via USB)
General	Power supply	12V/4A
	Power Consumption	<15W (without HDD)
	Working environment	Temperature:0°C—+55°C, Humidity:10%—90%, Atm:86kpa—106kpa
	Dimension	178mm*87mm
	Weight	140g



www.iid2secure.nl

Extra Benefits, Less Price

Finestrat, 19, 03530 La Nucia, Alicante, Spain

© IID Secure Tech S.L.U. 2019

Heemtedestraat 16 Amsterdam, Netherlands

Support@iid2secure.nl

+31614762425

Data Subject to change without notice